

- ✓ UL844
- ✓ Wet Location, Enclosed and Gasketed
- ✓ IP Rating 65



Fixture Appearance

- Injection Polymeric Non-Metallic Fixture
- Durable Tempered Glass Lens

Electrical Characteristics

- Standard AC input: 120-277 VAC
- EMI filter: 47CFR, part 2, part 15
- Power factor: >.9
- Total harmonic distortion: <20%
- Surge protection: IEC/EN 61000-4-5 EMC test standard

LED Light Engine Characteristics

- L70 Rated life of 100,000+ hours
- Minimum CRI: 70
- Operating temp: -40° C to +65° C
- No toxic chemicals/ROHS compliant
- ETL certified, meets UL and CSA standards
- 50-90% energy savings
- Manufactured in the USA

Applications

- Petrochemical Facilities
- Solvent and Cleaning Areas
- Lubrication Pits
- Processing Plants
- Oil Drilling Rigs
- Water Treatment Plants
- Paint Manufacturing Plants

Warranty

- 5-year manufacturer's warranty
- U.S. manufacturing and quality control

Installation

- Licensed electrician required
- Contact Noribachi for additional support

Catalog Numbering System

FIXTURE	LIGHT ENGINE	COLOR	VOLTAGE	MOUNT
NHS04	024A	CW	MT	PNDT

Light Engine

024A	3,360 Lumens @ 24W
024B	5,040 Lumens @ 36W
024A-RED	1,488 Lumens @ 17W
024B-RED	2,232 Lumens @ 24W
024A-GREEN	2,736 Lumens @ 25W
024B-GREEN	1,432 Lumens @ 36W
024A-BLUE	1,097 Lumens @ 25W
024B-BLUE	1,645 Lumens @ 36W

Voltage

MT	Multi-Tap : Up to 277 VAC
347	347 VAC
480	480 VAC

Mount

PNDT	Pendant
CL	Ceiling
WM	Wall Mount

Color Temperature

WW	Warm White
NW	Neutral White
CW	Cool White
CC	Custom Color and/or Custom CRI

Dimensions

