

O Series

LED Explosion Proof Light

VENAS



Classifications:

- ◆ ATEX Marking
 - ◆ II 2 G Ex eb mb IIC T6 Gb
 - ◆ II 2 D Ex tb IIIC T80 Db IP66
- ◆ IECEx Marking
 - ◆ Ex Eb mb IIC T6 Gb
 - ◆ Ex tb IIIC T80 Db IP66
- ◆ UL844 Marking (North American)
 - ◆ Class I, Division 2, Groups A, B, C, D
 - ◆ Class II, Division 2, Groups E, F, G
 - ◆ Class II, Division 2, Groups F, G
 - ◆ Class III
- ◆ Marine Marking
 - ◆ UL 1598A
- ◆ Other Rating
 - ◆ IP66

Standard Materials:

- ◆ Housing: Copper free aluminum
- ◆ Lens: Tempered glass (frosted lens or clear lens are available.)

LED Explosion Proof Light - O Series


Key Features:

- ◆ Compact structure, small size and light weight for easy installation.
- ◆ High vibration and impact resistance.
- ◆ Protective metal cage against potential damage.
- ◆ Tempered glass for high heat resistance.
- ◆ Mounting ways: pendant, wall and end bracket mountings.
- ◆ Beam angles are optional: 40°/60°/90°/120°.
- ◆ Low temperature applications to -40°C (-40°F) and high temperature up to 60°C (140°F).
- ◆ Power Factor: > 0.9
- ◆ Outlet: regular 1 meter.
- ◆ Environmentally Friendly 50,000 hours lifespan.
- ◆ Waterproof and dust-proof, without internal cleaning and maintenance.
- ◆ 5-year warranty.

Applications:

- ◆ Oil and gas industry
 - All petroleum production and refining
 - Petroleum loading and transportation
 - Petroleum storage and retail
 - LNG industry
 - All mining operations and service
- ◆ Ocean, marine and aerospace field
 - Ocean platform operation facilities
 - Aerospace clean room and production
 - Ocean vessel operations
- ◆ Chemical industry
 - All types of paint facilities
 - Chemical production and storage
- ◆ Metal treatment
 - Steel and aluminum factories
 - Pumping stations in any environment
 - Metal smelting, foundry and fabrication
- ◆ Food and alcohol industry
 - Flour and fine particle production and storage
 - Food and distilling production
 - Alcohol industry

Ordering Guide:



- | | | | |
|---|---|---|---|
| <p>① PRODUCT CATEGORY</p> <ul style="list-style-type: none"> ◆ Explosion proof product | <p>② WATTAGE</p> <ul style="list-style-type: none"> ◆ 10W/20W/30W/40W | <p>③ PRODUCT SERIES</p> <ul style="list-style-type: none"> ◆ O= O Series | <p>④ DIMMING OPTION</p> <ul style="list-style-type: none"> ◆ D= Dimmable ◆ N= Non-dimmable |
| <p>⑤ CCT</p> <ul style="list-style-type: none"> ◆ Z can be 22, 30, ... 70. ◆ 22=2200K, 30=3000K, ..., 70=7000K | <p>⑥ BEAM ANGLE</p> <ul style="list-style-type: none"> ◆ D40= 40° ◆ D60= 60° ◆ D90= 90° ◆ D120= 120° | <p>⑦ GLASS INFORMATION</p> <ul style="list-style-type: none"> ◆ A can be "C", denotes Globe glass and wire guard, which are the standard parts of the end product. ◆ Frosted lens or clear lens are available. | <p>⑧ MOUNTING STYLE</p> <ul style="list-style-type: none"> ◆ M1: Ceiling Mounting ◆ M2: Pole Mounting ◆ M3: 90 Degree Wall Mounting |

LED Explosion Proof Light - O Series


Technical Data:

Model	Wattage	Operating Voltage	Total Lumens (lm)	CRI	CCT
EX-10W OYZDAM	10W	AC100-277/220-480V; DC12-36V	950	>70	2200K-7000K
EX-20W OYZDAM	20W	AC100-277/220-480V; DC12-36V	1,900	>70	2200K-7000K
EX-30W OYZDAM	30W	AC100-277/220-480V; DC12-36V	2,850	>70	2200K-7000K
EX-40W OYZDAM	40W	AC100-277/220-480V; DC12-36V	3,800	>70	2200K-7000K



Packing Information:

Model	Quantity/Carton	Packing Size	Net Weight	Gross Weight
EX-10W OYZDAM	1 PC	10.43x14.96x10.04inch	4.62kg/10.25lbs	5.4kg/11.90lbs
EX-20W OYZDAM	1 PC			
EX-30W OYZDAM	1 PC			
EX-40W OYZDAM	1 PC			

Photometry:



Dimensions: unit: mm[inch]




Dimension for Flat Guard
Thickness of glass: 4.5mm


LED Explosion Proof Light - O Series

Mounting: unit: mm[inch]


◆ Ceiling Mounting:



◆ Pole Mounting:




◆ 90° Wall Mounting:



LED Explosion Proof Light - O Series

Mounting: unit: mm[inch]

90° Walling Mounting with Reflector:



Accessories:



Pendent



Ceiling/Wall



Ceiling/Wall (Interior Detail)



Wall Elbow



Reflector



Extension



Globe Glass



Globe Guard



Heat Sink



Clear



Flat Glass



Flat Guard



Main Part